



Two Post Lifts

LIGHT and HEAVY DUTY SERVICE

Dependable **Symmetric** **PRODUCTIVE** Experience **Reliable**
VERSATILE **FASTER** BATTERY
 SPEED Original **TRUSTED** **LEADER** **TESTED** Raised in Madison
 Buy America **TRIO** Global Leader **SHOCKWAVE** **PERFORMANCE** **LEGENDARY**
 Asymmetric **Efficient** **Service** **Robust**
VALUE **Pride** **Innovative** **Long-Lasting**



www.rotarylif.com



Shown: SPO20U0T0RD 20,000 lbs. capacity SHOCKWAVE-equipped lift with TRIO arms



Rotary SPOA10 Series ASYMMETRIC LIFTS

ENGINEERED FOR CARS and LIGHT TRUCKS **10,000 lbs. CAPACITIES**

Rotary's versatile asymmetric two-post lift is the only lift you'll ever need.

With options at every turn, you can customize the SPOA10 series to fit the needs of your shop and your techs.

Choose your:


- Arm configuration
- Adapter type
- Lift height
- Power option
- Productivity accessories

Lifts feature:

- Original "Double S" column design
- Performance tested to 20,000 cycles
- Nationwide support
- ALI Gold Certified

True Asymmetrical Lifts

Columns are rotated 30° allowing maximum door opening on passenger cars for improved access to vehicle interior. This column rotation places the approximate center of gravity of the vehicle in line with the optimum load capability of the column, reducing unnecessary wear and tear on the column, carriage, and bearings.



ASYMMETRIC LIFT SPECIFICATIONS

WITH SHOCKWAVE

Overall Height: 11' 8-1/2' / 12' 4-1/2"

Overall Width: 11' 5-3/8"

Drive-thru: 95 1/4"

Inside Columns: 107 1/4"

Min. Bay Size: 12' x 24'

Ceiling Height Min: 12' / 12' 6"

Motor / Voltage 10: 2 HP, 208-230V / 5 HP, 110V*

Time of Full Rise and Descent: 45 seconds / 40 seconds
25 seconds / 19 seconds*

*Actual rise and descent times vary depending on vehicle weight.



MODEL SHOWN:
SPOA10N700BL



MODEL SHOWN:
SPOA10N800BL



MODEL SHOWN:
SPOA10N8G0RD

SPOA10

Standard 2-stage arms with exclusive three-position flip-up FA adapters

Flip-up adapters

feature great strength in a simple design. The entire assembly is joined with a single pin providing stable support in any position.



SPOA10 TRIO™

Includes TRIO™ 2-piece, three-stage arms with the choice of two adapter options / models

Patented two-piece, three-stage TRIO™ asymmetrical arms have a lower profile making spotting a vehicle fast and easy with better vehicle protection. The arms are lower than the poly-covered adapters providing clearance for vehicle panels and ground effects. Choose the best adapter set for each vehicle to be repaired all on the same arm.†



SPOA10-FA-TRIO



SPOA10-TA-TRIO



SPOA10-RA-TRIO

SPOA10-TRIO™ SW

SHOCKWAVE-EQUIPPED POWER

Includes TRIO™ 2-piece, three-stage arms plus exclusive DC SHOCKWAVE™ power with onboard 110v charger

SUPERCHARGE 2-POST LIFTS WITH SHOCKWAVE™



Dramatically accelerate productivity with Shockwave™. Rotary's exclusive Shockwave™ technology produces cycle times that are twice as fast as standard lifts. And with its Spotline™ laser that shoots down the hood and dash, centering and spotting a vehicle couldn't be easier. Shockwave's patent pending DC power system gives you lower cost and more reliable operation while using two standard Group 24 batteries.† Shockwave's built in battery charger uses 110v power, eliminating the need for expensive 220v wiring resulting in an installation savings of 80% or more. And, if your shop loses power, SHOCKWAVE-equipped lifts keep working.

Available on select 7,000 to 20,000 lbs. capacity lifts.



SCAN THIS VIDEO CODE TO LEARN ABOUT THE BENEFITS OF ROTARY SHOCKWAVE LIFTS

†Batteries are not included

Select product photography is shown with optional accessories that are not standard with each lift purchase.

† EACH ADDITIONAL ADAPTER SET IS SOLD SEPARATELY

ASYMMETRIC LIFT MODELS


BL = Blue / RD = Red



CONVENTIONAL 2-STAGE ARMS
Flip Up Adapters (FA)



THREE-STAGE TRIO ARMS
Flip Up Adapters (FA)



THREE-STAGE TRIO ARMS
Truck Adapters (TA)



THREE-STAGE TRIO ARMS
Round Adapters (RA)

	STANDARD	SPOA10N700BL SPOA10N700RD	SPOA10N800BL SPOA10N800RD	SPOA10N8T0BL SPOA10N8T0RD	SPOA10N8G0BL SPOA10N8G0RD
SHOCKWAVE EQUIPPED		SPOA10U705BL SPOA10U705RD	SPOA10U805BL SPOA10U805RD	SPOA10U8T5BL SPOA10U8T5RD	SPOA10U8G5BL SPOA10U8G5RD
Rise*	STANDARD SHOCKWAVE	72 3/4" - 78 3/8" 75 3/4" - 81 3/8"	72 3/4" to 78 3/8" 75 3/4" to 81 3/8"	72 1/8" to 73 3/8" 75 1/8" to 76 3/8"	72 1/16" to 73 5/16" 75 1/16" to 76 5/16"
Front Arm Min/Max		20 1/2" - 40 3/4"	21 1/4" / 43 1/2"	20 1/2" / 40 3/4"	20 1/2" / 40 3/4"
Rear Arm Min/Max		40 1/4" - 60 7/8"	32 3/4" / 61"	34 1/2" / 58 1/4"	34 1/2" / 58 1/4"
Min Adapter Height		4 3/4"	4 3/4"	4 1/8"	4 1/16"

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke. Heights and widths reflect standard settings. SPOA10 lift colors come standard with your choice of red or blue.

Rotary SPO10 Series SYMMETRIC LIFTS

ENGINEERED FOR CARS and LIGHT TRUCKS **10,000 lbs. CAPACITIES**

Trust the industry standard symmetrical two post lift.

For over 30 years, Rotary Lift has built quality into every two-post we've designed. With industry-leading features, the SPO10 delivers everything your shop needs.

Choose your:


- Arm configuration
- Adapter type
- Lift height
- Power option
- Productivity accessories

Lifts feature:

- Original "Double S" column design
- Performance tested to 20,000 cycles
- Nationwide support
- ALI Gold Certified

True Symmetrical Lifts

Lift columns are not rotated providing more width between columns to accommodate larger vehicles and improve vehicle access - allows max door opening on trucks and vans for access to vehicle interior.



Vehicle load is centered between the columns to maximize lifting capacity

SYMMETRIC LIFT SPECIFICATIONS *WITH SHOCKWAVE

Overall Height: 11' 8-1/2" / 12' 4-1/2"

Overall Width: 11' 5-5/8"

Drive-thru: 102 1/2"

Inside Columns: 114 3/4"

Min. Bay Size: 12' x 24'

Ceiling Height Min: 12' / 12' 6"

Motor / Voltage 1Ø: 2 HP, 208-230V / 5 HP, 110V*

Time of Full Rise and Descent: 45 seconds / 40 seconds
25 seconds / 19 seconds*

* Actual rise and descent times vary depending on vehicle weight.



MODEL SHOWN: SPO10N700BL



MODEL SHOWN: SPO10U705RD



MODEL SHOWN: SPO10N800BL

SPO10

Standard 2-stage arms with exclusive three-position flip-up FA adapters

Flip-up adapters feature great strength in a simple design. The entire assembly is joined with a single pin providing stable support in any position.



Select product photography is shown with optional accessories that are not standard with each lift purchase.

SPO10-SW

SHOCKWAVE-EQUIPPED POWER Includes 2-stage conventional arms plus exclusive DC SHOCKWAVE™ power with onboard 110v charger

Two times faster than any other standard service lift. Achieve your goals of greater technician productivity and higher profits. Designed specifically for bays where service speed is essential.



SPO10 TRIO™

Includes TRIO™ 2-piece, three-stage arms with exclusive FA three-position adapters



SPO10 RA

3-stage conventional arms with thread-up padded RA adapters. Optional SHOCKWAVE™ power available.

RA adapters are round padded polymer adapters that thread-up for additional positioning.



SPO10 TA

3-stage conventional arms with thread-up padded TA adapters. Optional SHOCKWAVE™ power available.

TA adapters are frame-engaging padded polymer adapters that thread-up for additional adapter reach.



SYMMETRIC LIFT MODELS BL = Blue / RD = Red	CONVENTIONAL 2-STAGE ARMS Flip Up Adapters (FA)	THREE-STAGE TRIO ARMS Flip Up Adapters (FA)	CONVENTIONAL 3-STAGE ARMS Truck Adapters (TA)	CONVENTIONAL 3-STAGE ARMS Round Adapters (RA)
---	--	--	--	--

STANDARD	SPO10N700BL SPO10N700RD	SPO10N800BL SPO10N800RD	SPO10N5T0BL SPO10N5T0RD	SPO10N5G0BL SPO10N5G0RD
SHOCKWAVE EQUIPPED	SPO10U705BL SPO10U705RD	SPO10U805BL SPO10U805RD	SPO10U5T5BL SPO10U5T5RD	SPO10U5G5BL SPO10U5G5RD
Rise*	STANDARD: 72 5/8" - 78 1/8" SHOCKWAVE: 75 5/8" - 81 1/8"	72 3/4" to 78 1/4" 75 3/4" to 81 1/4"	72 11/16" to 75 3/16" 75 11/16" to 78 3/16"	72 1/2" to 74 3/4" 75 1/2" to 77 3/4"
Front Arm Min/Max	31" - 54"	30 1/2" - 54 7/8"	27 1/2" / 59"	27 1/2" / 59"
Rear Arm Min/Max	31" - 54"	30 1/2" - 54 7/8"	27 1/2" / 59"	27 1/2" / 59"
Min Adapter Height	4 5/8"	4 3/4"	4 11/16"	4 1/2"

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke. Heights and widths reflect standard settings.
** Actual rise and descent times vary depending on vehicle weight. SPO10 lift colors come standard with your choice of red or blue.



7,000 lbs. Capacity Lift Series

SPECIALTY LIFTS ENGINEERED FOR PRODUCTIVITY AND SAFETY



MODEL SHOWN:
SPOA7N6X0BL



SPOA7-MP MODELS

BL = Blue / RD = Red

ADJUSTABLE
PAD LIFT
Movable Pads (MP)

STANDARD		SPOA7N6X0BL SPOA7N6X0RD
SHOCKWAVE EQUIPPED		SPOA7U6X5BL SPOA7U6X5RD
Rise*	STANDARD SHOCKWAVE	70 5/8" to 73 5/8" 73 5/8" to 76 5/8"
Overall Height		11' 8 1/2"
Overall Width		11' 5 3/8"
Drive-thru		78 1/8"
Inside Columns		107 1/4"
Pad Length Overall Retracted / Extended		71 1/8" to 87 1/4"
Min/Max Inside Distance Between Pads		39 7/8" - 56"
Min Pad Height		2 5/8"
Min Bay Size		12' X 24'
Ceiling Height Min With SHOCKWAVE		12' 12' 6"
Motor / Voltage With SHOCKWAVE		2 HP, 208-230V 5 HP / 110V
Time of Rise / Descent With SHOCKWAVE**		45 / 40 seconds 25 / 19 seconds

SPOA7-MP

Quick service pad lift - low profile, drive-over adjustable pads spot vehicles quickly and accurately. Perfect for a quick-lube bay.

- 7,000 lbs. capacity
- 4 adjustable lift height options
- Available with SHOCKWAVE™ power
- Original "Double S" column design
- ALI Gold Certified

Improve vehicle reach with adjustable drive-over pads with hinged approach ramps



Rubber spacer blocks provide clearance

Four (4) each 1.5" and 3" blocks included

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke
 ** Times vary depending on vehicle weight
 Heights and widths reflect standard settings



MODEL SHOWN:
SPOA7N5L0BL



SPOA7-LPA MODELS

BL = Blue / RD = Red

LOW PROFILE
2-STAGE ARMS
Round Adapters (RA)

STANDARD		SPOA7N5L0BL SPOA7N5L0RD
SHOCKWAVE EQUIPPED		SPOA7U6L5BL SPOA7U6L5RD
Rise*	STANDARD SHOCKWAVE	71 3/8" to 73 5/8" 74 3/8" to 76 5/8"
Overall Height With SHOCKWAVE		11' 8 1/2" 12' 4-1/2"
Overall Width		11' 5 3/8"
Drive-thru		95 1/4"
Inside Columns		107 1/4"
Front Arm Min/Max		23 1/4" / 33 1/2"
Rear Arm Min/Max		33 1/2" / 54 3/4"
Min Adapter Height		3 3/8"
Min Bay Size		12' X 24'
Ceiling Height Min With SHOCKWAVE		12' 12' 6"
Motor / Voltage With SHOCKWAVE		2 HP, 208-230V 5 HP / 110V
Time of Rise / Descent With SHOCKWAVE**		45 / 40 seconds 25 / 19 seconds

SPOA7-LPA

Asymmetric lift with slimmer, ultra-low profile 2-stage arms. Arms are designed with a wider stance for greater clearance to lift low profile vehicles.

- 7,000 lbs. capacity
- Round, thread-up RA adapters
- 4 adjustable lift height options
- Available with SHOCKWAVE™ power
- Original "Double S" column design
- Multi-position wheel spotting dish
- ALI Gold Certified



The minimum arm reach, overall arm sweep and shorter arm gusset allows precise spotting to lift compact profile vehicles.

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke
 ** Times vary depending on vehicle weight
 Heights and widths reflect standard settings



ATO77

Lift available in blue only

3-STAGE
FRONT ARMS
2-STAGE
REAR ARMS
Round Adapters (RA)

STANDARD		ATO77N000MBL
Rise*		71 3/4" - 74"
Overall Height		11' 8 1/8"
Overall Width		10' 2 7/8"
Drive-thru		92 1/8"
Inside Columns		100 5/8"
Front Arm Min/Max		21 1/8" / 43 1/2"
Rear Arm Min/Max		32" / 58 1/8"
Min Adapter Height		3 3/4"
Min Bay Size		11' X 24'
Ceiling Height Min		12'
Motor / Voltage		2 HP, 208-230V
Time of Rise Time of Descent		45 seconds 40 seconds

ATO77


Space-saving asymmetric lift designed for maximum drive-thru clearance with minimal footprint. Over 14" narrower than standard two post lift - fits in a 11' wide bay. Power unit mounts on either side of lift - enter vehicles from either front or back of lift.

- 7,700 lbs. capacity
- 3-stage front arms / 2-stage rear arms with thread-up RA adapters
- Four (4) each adapter extensions at 3 1/2" and 5 1/8"
- Multi-position wheel spotting dish

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke



MODEL SHOWN:
TLO7N560BL



TLO7

BL = Blue / RD = Red

Adjustable
Ramps
and Rails

STANDARD		TLO7N560BL TLO7N560RD
Rise*		68 3/8"
Overall Height		11' 8 1/2"
Overall Width		11' 5 5/8"
Drive-thru		91"
Inside Columns		114 1/2"
Min/Max Wheelbase		30" / 88"
Tire Fork Length		13"
Min Width Inside Tires		20 1/2"
Extended Width		13' 9"
Min Bay Size		12' X 24'
Ceiling Height Min		12'
Motor / Voltage		2 HP, 208-230V
Time of Rise Time of Descent		45 seconds 40 seconds

TLO7

Symmetrical turf maintenance lift. Service three and four wheel turf equipment and golf carts. Drive-over ramps and side rails provide the width and support of wide equipment. Can be converted to lift passenger cars and light trucks with optional arm kits.

- 7,000 lbs. capacity
- 3 adjustable lift height options
- Accommodates a 30" wheelbase
- Versatile small wheel attachment
- Wheel engaging - chocks wheels automatically
- Provides easy access to reels and hydraulic systems

* Rise measures the highest position of the arm rail from floor to full cylinder stroke.
 Heights and widths reflect standard settings.



SP012 Series SYMMETRIC LIFTS

ENGINEERED FOR MEDIUM DUTY LIFTING **12,000 lbs. CAPACITIES**

The SP012 Series lifts: you can't find a better designed and better engineered medium-duty lift.

Its size, wider drive-thru and larger footprint make it optimal for shops that work on taller, heavier vehicles. And that's why it's chosen by more dealers and independent repair shops than any other lift in its category.

Choose your:

- Lift height and width
- Power option
- Productivity accessories



SHOWN: SP012X

Standard with three-stage arms and polymer Truck Adapters primarily used on framed vehicles.

Adjustable adapters thread-up and come with stackable inserts and storage rack. No metal to metal contact.



LIFT FEATURES

- Three-stage arms for greater reach
- Original "Double S" column design
- Performance tested to 20,000 lift cycles
- Nationwide support
- ALI Gold Certified

SP012 WIDE

Wider stance designed to provide an additional 17" of drive-thru width for larger trucks and vans.

Wide lift design provides the versatility for greater under vehicle access and less obstruction for service to battery electric vehicles.

SP012-LC

LOW CEILING DESIGN

Shorter overhead height designed for shops with lower ceiling bays.

- 11' 8" overall height
- 11' 9" minimum required ceiling height

Product photography is shown with optional accessories that are not standard with each lift purchase.

SP012-TA

Symmetric lift with TA truck adapters and 3-stage arms for greater vehicle reach.

SP012-SW

SHOCKWAVE-EQUIPPED POWER

Includes SHOCKWAVE™ DC power with onboard 110v charger providing 2X the lifting speed of conventional lifts.

Standard SP012 and SP012-SW lifts are available in 4 adjustable lift height options / models

ADD UP TO 3' OF ADDITIONAL HEIGHT FOR EURO-STYLE CARGO VANS



Model shown: SP012U7T8RD SHOCKWAVE-powered lift with optional accessories and additional equipment

SYMMETRIC LIFT MODELS

BL = Blue / RD = Red



CONVENTIONAL 3-STAGE ARMS
Truck Adapters (TA)



CONVENTIONAL 3-STAGE ARMS
Truck Adapters (TA)



CONVENTIONAL 3-STAGE ARMS
Truck Adapters (TA)

	STANDARD POWER	STANDARD MODEL SP012N7T5BL SP012N7T5RD	LOW CEILING MODEL SP012N7TLBL SP012N7TLRD	WIDE MODEL SP012N7W6BL SP012N7W6RD
SHOCKWAVE EQUIPPED		SP012U7T5BL SP012U7T5RD	N/A	N/A
Rise*	STANDARD SHOCKWAVE	75 3/4" - 78 1/8" 75 3/4" - 78 1/8"	75 3/4" - 78 1/8" N/A	75 3/4" - 78 1/8" N/A
Overall Height		13' 8"	11' 8"	13' 11-1/2"
Overall Width		11' 5-5/8"	11' 5-5/8"	12' 10-5/8"
Drive-thru		102 3/8"	102 3/8"	119 3/8"
Inside Columns		114 7/8"	114 7/8"	131 7/8"
Front Arm Min/Max		27 1/2" / 59"		
Rear Arm Min/Max		27 1/2" / 59"		
Min Adapter Height		4 3/4"		
Min Bay Size		12' x 26'	12' x 26'	14' x 26'
Ceiling Height Min		13' 9"	11' 9"	14' 1/2"
Motor / Voltage 1Ø		2 HP, 208-230V / 5 HP - 110V with SHOCKWAVE		
Time of Full Rise		60 seconds / 25 seconds with SHOCKWAVE		

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke.

** Actual rise and descent times vary depending on vehicle weight. Heights and widths reflect standard settings. SP012 lift colors come standard with your choice of red or blue.

Rotary SPO16/20 Series SYMMETRIC LIFTS

SUPER DUTY LIFTS WITH TRIO ARMS **16/20,000 lbs. CAPACITIES**

Pick up class 1 through class 5 vehicles with Rotary versatility.†

Super duty symmetric lifts with industry-leading versatility; pick up a greater variety of vehicles faster and easier than any lift of it's kind.‡

Combine high capacity lifting, a low-profile stance, wider installation options and expanded arm reach possibilities and pick up a broad range of vehicles by choosing:

- Lift height and width
- Power options



WATCH AND LEARN ABOUT SPO20 LIFTS

Adjustable, thread-up adapters for easy vehicle contact

Standard with set of four (4) clip-on rubber pads for passenger cars and 10" (2 each) and 5" (4 each) stackable adapter extensions.



Optional round rubber adapters available.

Adjustable adapters designed for unibody vehicles.
LIFTING CAPACITY: 11,000 lbs.



LIFT FEATURES

- Patented three-stage TRIO™ arms with adjustable truck adapters
- Original "Double S" column
- Two height options
- Three width configurations
- 20 second lowering time
- ALI Gold Certified



MODEL SHOWN: SPO160T0BL



MODEL SHOWN: SPO20U0T0RD

SPO16-LC / 20-LC

LOW CEILING MODELS

Designed for shops with lower ceiling bays.


- Height range: 13' 6" to 14' 6"
- Available with SHOCKWAVE™ DC battery power

SPO16 CARGO

Standard 3-stage arm configuration designed to service longer van wheelbases and spot specific pickup points.

- 2 lift height options including low ceiling model

Minimum / Maximum arm reach:
36 13/16" to 74 13/16"



Shown with adjustable thread up adapters

SPO16 / 20

Symmetric super-duty lift with 3-stage TRIO™ arms for greater vehicle reach.

SPO16-SW / 20-SW

SHOCKWAVE-EQUIPPED POWER Includes SHOCKWAVE™ DC power providing 2X the lifting speed of conventional lifts.

SYMMETRIC LIFT MODELS

BL = Blue / RD = Red



THREE-STAGE TRIO ARMS
Thread Up Adapters



THREE-STAGE TRIO ARMS
Thread Up Adapters



CONVENTIONAL 3-STAGE ARMS
Thread Up Adapters



CONVENTIONAL 3-STAGE ARMS
Thread Up Adapters



THREE-STAGE TRIO ARMS
Thread Up Adapters



THREE-STAGE TRIO ARMS
Thread Up Adapters

STANDARD POWER	STANDARD MODEL SPO16N0T0BL SPO16N0T0RD	LOW CEILING MODEL SPO16N0TLBL SPO16N0TLRD	CARGO MODEL SPO16N0A0BL SPO16N0A0RD	CARGO LOW CEILING SPO16N0ALBL SPO16N0ALRD	STANDARD MODEL SPO20N0T0BL SPO20N0T0RD	LOW CEILING MODEL SPO20N0TLBL SPO20N0TLRD
SHOCKWAVE EQUIPPED	SPO16U0T0BL SPO16U0T0RD	SPO16U0TLBL SPO16U0TLRD	SPO16U0A0BL SPO16U0A0RD	SPO16U0ALBL SPO16U0ALRD	SPO20U0T0BL SPO20U0T0RD	SPO20U0TLBL SPO20U0TLRD
Lifting Capacity	16,000 lbs.	16,000 lbs.	16,000 lbs.	16,000 lbs.	20,000 lbs.	20,000 lbs.
Rise*	77 31/32" - 80 1/32"	77 31/32" - 80 1/32"	77 13/32" - 78 13/32"	77 13/32" - 78 13/32"	77 31/32" - 80 1/32"	77 31/32" - 80 1/32"
Overall Height	15' to 16' 6"	13' 6" to 14' 6"	15' to 16' 6"	13' 6" to 14' 6"	15' to 16' 6"	13' 6" to 14' 6"
Overall Width	NARROW: 12' 11" / STANDARD: 13' 5" / WIDE: 13' 11"					
Drive-thru	NARROW: 105 11/32" / STANDARD: 111 11/32" / WIDE: 117 11/32"					
Inside Columns	NARROW: 120 15/32" / STANDARD: 126 15/32" / WIDE: 132 15/32"					
Front Arm Min/Max	34 11/16" / 64"	34 11/16" / 64"	36 13/16" - 74 13/16"	36 13/16" - 74 13/16"	34 11/16" / 64"	34 11/16" / 64"
Rear Arm Min/Max	34 11/16" / 64"	34 11/16" / 64"	36 13/16" - 74 13/16"	36 13/16" - 74 13/16"	34 11/16" / 64"	34 11/16" / 64"
Min Adapter Height	5 31/32"	5 31/32"	5 13/32"	5 13/32"	5 31/32"	5 31/32"
Min Bay Size	15' x 30'					
Ceiling Height Min	15' 2" to 16' 8"	13' 8" to 14' 8"	15' 2" to 16' 8"	13' 8" to 14' 8"	15' 2" to 16' 8"	13' 8" to 14' 8"
Motor / Voltage 1Ø	SPO16: 2 HP, 208-230V / SPO20: 4 HP, 208-230V / 5 HP - 110V with SHOCKWAVE					
Time of Full Rise**	81 seconds / 60 seconds at full capacity / 33 seconds at half capacity with SHOCKWAVE					

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke. ** Actual rise and descent times vary depending on vehicle weight. SPO16 / 20 lift colors come standard with your choice of red or blue.

† NOTE: Level bay floors provide the best underbody clearance needed to accommodate the broadest range of vehicles to spot and lift. Wide setting installations create the best tire clearance on shorter wheelbases. Vehicle axle weight MUST NOT EXCEED one half of total lift capability. Maximum arm load is 1/4 of lift rated capacity. SPO16/20 lifts are designed for most class 4 and 5 vehicles. Some vehicles within each class may exceed arm capacity but not the lift capacity. Please consult vehicle axle information and lift manual for more information.

OPTIONAL 2-POST LIFT ACCESSORIES

FA Three-Position Flip-Up Adapter for 3-Stage TRIO™ Arms

KIT #T100274

For 10,000 lbs. capacity lifts. Allows for quick positioning on a variety of pick-up points.



RA Adapter for 3-Stage TRIO™ Arms

KIT #T100272 Set of four (4) FJ6219 polymer pad round adapters. 10,000 lbs. capacity adapters thread-up to allow protection of the vehicle underbody for no metal to metal contact. Also available for use with stackable inserts.



RA Adapter for Conventional 3-Stage Arms

KIT #FJ6225 for 10,000 lbs. capacity lifts. Set of four (4) FJ6202 polymer pad round adapters.

TA Thread-Up Adapter for 3-Stage TRIO™ Arms

KIT #T100273 includes four (4) T110564 adjustable truck adapters with rubber pads. Required use when lifting trucks and frame vehicles. Also available for use with stackable inserts. For 10,000 lbs. capacity lifts.



TA Thread-Up for Conventional 3-Stage Arms

KIT #FJ6197 includes (4) FJ6214 adapters for 10,000 lbs. capacity lifts with standard arms.

Adapter Extensions

Adapter kit #T100271

Fits TRIO models SPOA10 RA / TA

Adapter kit #FJ7880BBK

Fits models SPO10 RA / TA and SPO12TA

Kits include four 3 1/2" and four 5" adapter extensions, mounting rack and hardware. Provides additional lifting height when vehicles require additional clearance or use on front or rear to level vehicle on lift.



Auxiliary Height Adapter Kits for FA Three-Position Flip-Up Adapters

Add 14 3/8" to 17 3/8" of additional overall adapter height. For use when raising certain vans or pickups. Includes four adapters, mounting rack and hardware. 2,500 lbs. capacity per adapter.

FJ6115BK

Adds 9 3/8" of height. Includes (4) adapters

#FJ6212KITYL

Shorter version. Adds 7 3/8" of height. Includes 4 adapters



Polymer Pad Adapter Kits for FA Adapters

Rubber contact surface protects undercoated surfaces. Includes four adapters, mounting rack and hardware. 2,500 lbs. capacity per adapter.

#FJ6138BK
Adds 1/2"



#FJ6190YL
Adds 1"



#FJ6139BK
Adds 2 1/2"



Specialty Adapters for GM Pickup Trucks



Extended Height Adapter for FA Adapters

#FJ6259KIT Flip Up Adapter Extensions

Adapter extensions for lifting 2019 Chevrolet Silverado and GMC Sierra 1500 trucks.

Four extensions for any lift with flip up adapters.

Kit includes (2) wide front adapters, (2) standard width rear adapters to keep the vehicle level.

- Maximum overall height: 9 11/32"
- Capacity 2,500 lbs. per adapter

Drop-In Truck Adapter Kits for Standard and TRIO™ Arms

Adapter kits for lifting 2019 Chevrolet Silverado and GMC Sierra 1500 trucks.

- Maximum width: 7"
- Capacity 3,000 lbs. per adapter



#FJ6258KIT

Set of two for standard 2 or 3 stage arms.

These adapters are wider to fit the wider frame of the vehicle. You'll replace the front two adapters on the lift and continue to use the current truck adapters on the rear arm.

#FJ6257KIT

Set of two specifically designed for TRIO arms.

Air / Utility Box

Column mounted. Provides quick access to utilities. Includes two 110V electric outlets, air connection with filter/regulator/lubricator.

SHOWN: #FA5911BK



Adapters and Organizer Rack Kits

Accommodate more vehicles with more adapters plus keep them organized.

SHOWN: #FJ6100BK

Four FJ696, four FJ697 and four FJ698 adapters plus column or wall-mounted adapter organizer rack (FJ6108)

Available in different configurations. Consult factory for options.

Patented Tool Holder

Keeps air guns, torque sticks, and other tools within easy reach. Mounts into pre-drilled column holes.

#FA5191E



Wheel Wing™ Tire Arm

100 lbs. capacity Wheel Wing tire arm mounts on column arm and holds a tire at lift arm height. Folds away when not in use.

- Adjustable to fit various lift arms
- Includes set of 2 arms, 2 magnetic lug nut dishes, shims

#FA5974



MW-200 Tire Lift

Air operated tire and wheel lift. 200 lbs. capacity.

- Quick transfers to tire balancers with easy positioning of the tire and wheel
- Includes air hose and air tool connection

#MW-200



#MW-500

500 lbs. capacity model available

RS4 Adjustable Jack Stands

4,000 lbs. CAPACITY

Maximum height: 84"

Minimum height: 55 1/2"

Fine thread-up height: 1 5/8" to 7 1/8"

#RS4



SPOTLINE™ Laser Kit

Motion activated laser helps center vehicles in bays quickly and accurately. Laser guided system comes complete with motion sensor and mounting hardware.



#FA7815

TECH LIGHT™ Line Light 2

Attach the 2 ultra slim light wands to columns for effective, 2-post lighting where you need it. Supplied with 4 magnetic clips for easy positioning on columns.

Includes:

- (2) 96 LED lights with 25' of cable and 20W power supply
- 3' spiral cords - stretches to 16" for placement under vehicle
- Magnetic junction box
- Input voltage 100-240 V AC
- Each measures 34"

#FA5701



TECH LIGHT™ Line Light R

Rechargeable LED inspection hand lamp with top spot light. Supplied with flexible suspension clips holder with both hook and magnet for positioning the light where you need it.

Additional suspension solutions available as accessories.

- 180 lumen in main light operates for up to 3 hours
- 120 lumen in spot light operates for up to 6 hours
- 4 hour charging time

#FA5702



Lock Light™ Patent pending

Provides an instant green light visual confirmation when lift is lowered to its locks. Compatible with high-pressure lifts that use an electric/hydraulic power unit providing an unused pressure port is available.

Kit includes:

- Indicator light assembly
- Pressure switch
- Mounting bracket
- 10' of electrical wire

#FA834-KIT / 110V

#FA835-KIT / 220V



Extended Height Kits

Raise the overhead clearance on 10,000 and 12,000 lbs. capacity two-post lifts. Kits includes column extensions and hardware.

CONSULT FACTORY FOR OPTIONS



Door Defender™

Solid rubber guard designed to fit over the two-post lift carriage. Enter and exit the vehicle without vehicle damage. Includes one (1) padded defender and adhesive.

#N823



Column Base Plate Cover

Covers the base plates keeping mounting hardware hidden, safely enclosed and protected.

Fits standard SPOA10, SPOA9 and SPOA7 (200 series and above) lifts.

#N539



Supercharged SHOCKWAVE™ Equipped Rotary Lifts:

The World's Fastest
and Most Trusted Lift
- and they're only
available from Rotary.



Twice as fast than any other standard service lift,
Shockwave-equipped lifts help achieve your goals
of greater technician productivity and higher profits.

Designed specifically for bays where service speed is essential, Shockwave helps you keep step with the everchanging demands in the vehicle service industry. Watch your productivity increase, the number of service orders increase and be shocked at the increase in revenue!

Available on 7,000 to
20,000 lbs. capacity lifts.



WATCH AND
LEARN ABOUT
SHOCKWAVE

TRIO™ Series Lifts: Innovating...Not Imitating

Rotary has reinvented the standard, combining
legendary quality construction with the most
advanced arm design on the market today.

Discover the TRIO™ arm's industry exclusive advantage: two arm configurations in one low-profile arm. Rotary's patented two-piece, three-stage asymmetrical arm design accommodates a wide range of vehicles and adapters are interchangeable with two vehicle contact options.* Exclusive TRIO™ arms feature a fast setup without moving heavy two or three inner arms and the integrated "third stage" adjustment easily and quickly slides the adapter to a pinpoint vehicle contact location.

*EACH ADDITIONAL ADAPTER
SET IS SOLD SEPARATELY



WATCH AND
LEARN ABOUT
TRIO LIFTS

Rotary Lift

2700 Lanier Drive / Madison, IN 47250, USA

rotarylif.com     

Sales:

1.812.273.1622 / 800.445.5438
insidesales@vsgdover.com

Government Sales:

800.445.5438 X5655

For additional information:

rotarylif.com/Government-Purchasing-Assistance/



Tech. Support:

800.445.5438
technicalsupport@rotarylif.com

Rotary Two Post Lifts

We revolutionized the two-
post lift, and we just continue
to make them better.

Rotary is the world's leading manufacturer of two-post lifts. We tirelessly pursue better design and improved, technician friendly operation to help your shop run better and turn higher profits.

The most expensive lift is the one that
doesn't work.

You can trust the fact that no brand of lift performs better or longer than Rotary. A lower price doesn't necessarily mean you're getting a lift for less. Our lifts are investments that pay for themselves quickly and boost your business for years to come. Rotary lifts cost less to operate, have a consistent track record of uptime with lower repair costs and are manufactured with nearly 95 years of legendary quality.

Rotary lifts are engineered, tested, and supported with pride in Madison, IN USA. Crafted by people who love what they do delivering their best work to you – our customer.

Choose the right lift for your shop.

Rotary Lift.



WATCH AND
LEARN ABOUT
TWO POST LIFTS

Lit# Rotary 2Post LD HD Brochure.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY LIFT, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Manufactured using the following patents:
Trio Arms™ / US Patent No. 8,973,712 / US Patent No. 9,550,658

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

