

SPO12-AV

WIDER DRIVE-THRU AND LARGER FOOTPRINT FOR SHOPS WORKING ON TALLER, HEAVIER VEHICLES

Wide design provides the drive-thru clearance for greater under vehicle access and less obstruction for service to battery electric vehicles.

Standard with adjustable TA truck and RA round poly adapters for use on framed and unibody vehicles.



Includes (4 each) 3 1/2" and 5" adapter extensions plus storage rack.

OPTIONAL LIFT CONFIGURATIONS

5 HEIGHT OPTIONS add up to 3' of additional height for taller cargo vans

STANDARD HEIGHT: 13' 8"
+1' to 14' 8" / +2' to 15' 8" / +3' to 16' 8"

LOW-CEILING HEIGHT: 11' 8"

3 STANDARD WIDTH OPTIONS enable up to 12" of additional drive-thru for wider vehicles: 11' 5-5/8", 11' 11-5/8", or 12' 5-5/8"

OPTIONAL WIDE OVERHEAD KIT #FJ71037 enables a 17" wider 12' 10-5/8" column stance. 8-1/2" lower lift overhead setting is used with this kit. Contact factory for details.



INCLUDES LOW-PROFILE AV ARMS[™] FOR ADDED REACH
SIMPLY LIFT ANYTHING!*

CHOOSE YOUR:

- Lift height and width
- Power option
- Productivity accessories

FEATURES:

- Rise height of over 75"
- Original "Double S" column
- Available with SHOCKWAVE[™] power
- ALI Gold Certified

SPECIFICATIONS

SPO12-AV

BL = Blue / RD = Red

STANDARD HEIGHT

SPO12N11M5BL/RD

LOW CEILING HEIGHT

SPO12N11MLBL/RD

Rise*	75 3/4" - 78 1/8"	
Overall Height	13' 8" STANDARD	11' 8" LOW
Overall Width	11' 5 5/8"	
Drive-thru	102 3/8"	
Inside Columns	114 7/8"	
Arm Reach Min/Max	27 3/8" / 59 1/8"	
Min. Adapter Height	4 5/8"	
Min. Bay Size	12' x 26'	
Min. Ceiling Height	13' 9" STANDARD	11' 10 3/4" LOW
Motor / Voltage 1Ø	2 HP, 208-230V	
Time of Full Rise	60 seconds	

Heights and widths reflect standard settings.

* Rise measures lowest and highest position of the supplied adapters from floor to full cylinder stroke.

** Rise and descent times vary depending on vehicle weight.



Model shown:

SPO12N11M5BL

★ WITHIN LIFT'S RATED CAPACITY AND VEHICLE CLEARANCE.



PART OF VSG a DOVER company

ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help: 800.445.5438

Sales: insidesales@rotarysolutions.com / Technical Support: HD-techsupport@rotarysolutions.com

ROTARY SOLUTIONS[™]

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.SPO12AV.Cutsheet.02.01.2026

©2026 VEHICLE SERVICE GROUP[™]

All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS[™], VEHICLE SERVICE GROUP[™], DOVER[®] and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.



EMAIL: SALES@CA-EQUIP.COM
PHONE: 919-231-8700



ROTARY SOLUTIONS

SERVING THE SHOP[™] SINCE 1925